

SUB 8003-AS II

ACTIVE SUBWOOFER

The SUB 8003 II active subwoofer features the latest generation of RCF woofer technology, digital amplifiers and DSP processing with higher power and enhanced performances. It offers the perfect blend of bass reproduction, high-pressure level and compact dimensions for mobile bands or DJs.

p.n. 130.00.432 (230 V)

p.n. 130.00.433 (115 V)



■ Club sound, DJs

■ Portable PA

■ Rental



RCF Precision's unique double silicone sealed spider design functions as an air pump expelling hot air and drawing in cool air every time the cone assembly moves.

- 2200 Watt
- 135 dB max SPL
- 40 Hz - 120 Hz frequency response
- 18" Woofer, 4.0" v.c.
- Selectable gain, X-over and delay
- Birch tour grade cabinet
- Stereo XLR input, Stereo XLR signal output



INNOVATIVE INPUT BOARD

The input board offers stereo xlr inputs and stereo xlr link-crossover outputs with switchable crossover frequencies for satellite systems. The system has a built-in DSP with selectable presets for perfect and easy adaptation to RCF's active 2-way speakers. Ideal for 12" or 15" active speakers from live sound series such as ART7, 4PRO and D-Line.



POWERFUL AMPLIFIER

4PRO 8003-AS II is equipped with a new generation of 2200 Watt Digital Amplifier that produce a very high output, an extremely low distortion and an incredible natural sound. The amplifier features a solid mechanical aluminum structure which not only stabilize the amplifier during transportation but also assist in the heat dissipation.