

SUB 905-AS II

ACTIVE SUBWOOFER

The SUB 905-AS II active subwoofer is ideal for building powerful subwoofer satellite systems where simultaneous compactness and high sound levels are required. The SUB 905-AS II has the most advanced RCF woofer technology, coupled with powerful digital amplifiers. It offers the perfect blend of bass reproduction, high-pressure level and compact dimensions for mobile bands or DJs.

p.n. 130.00.434 (230 V)

p.n. 130.40.435 (115 V)



■ Club sound, DJs

■ Portable PA

■ Rental



Subwoofers inside/outside voice coils represents the unreachable reference in power handling, their "triple thickness" former transfer the sound to the cone with extreme accuracy and reliability.

- 2200 Watt
- 133 dB max SPL
- 40 Hz - 120 Hz frequency response
- 15" Woofer, 3.0" v.c.
- Selectable gain, X-over and delay
- Birch tour grade cabinet
- Stereo XLR input, Stereo XLR signal output



INNOVATIVE INPUT BOARD

The input board offers stereo xlr inputs and stereo xlr link-crossover outputs with switchable crossover frequencies for satellite systems. The system has a built-in DSP with selectable presets for perfect and easy adaptation to RCF's active 2-way speakers. Ideal for 10", 12" or 15" active speakers from live sound series such as ART7, 4PRO and D-Line.

WOOFER MAGNETIC STRUCTURE

A strong magnetic structure guarantee dynamic and precision. Triple roll surround and spider design offer great linearity and precise reproduction

